

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

1 Identification

· Product identifier

HERCULAN EG 120 { A } · Trade name:

Article number: 701715/32

Application of the substance / the mixture Coating compound/ Surface coating/ paint

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

HERCULAN B.V.

Energieweg 6 4231 DJ Meerkerk The Netherlands Phone +31 183 354700 Fax: +31 183 354740 e-mail: info@herculan.com

Information department: Enviromental department

Emergency telephone number:

+49 (0) 6131 19240 [24 h - 365 d] - Giftinformationszentrale Mainz

+31 (0) 183 354 700 [Mo - Fr. 8 - 17 o'clock] - HERCULAN

2 Hazard(s) identification

Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms GHS08

Signal word Danger

Hazard-determining components of labeling: Quartz (SiO2)

Hazard statements

Precautionary statements

H350 May cause cancer.

Wear protective gloves/protective clothing/eye protection/face protection. P280

P201 Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501

Dispose of contents/container in accordance with local/regional/national/ international regulations.

· Classification system:

NFPA ratings (scale 0 - 4)

Health = 0

Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

0 Health = 0 Fire = 1 Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: There are no additional ingredients present which are classified as hazardous to health or the environment and on this basis need to be mentioned in this section.

(Contd. on page 2)

HERCUL

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN EG 120 { A }

(Contd. of page 1) · Dangerous components: 14808-60-7 Quartz (SiO2) 10 - 25% & Carc. 1A, H350 25322-69-4 Polypropylenglycol 5 - 10% Acute Tox. 4. H302 · Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· After swallowing:

· Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Generally the product does not irritate the skin.

· After eve contact:

If symptoms persist consult doctor.

· Information for doctor:

· Most important symptoms and effects, both

acute and delayed No further relevant information available

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

Suitable extinguishing agents:



CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

Rinse opened eye for several minutes under running water.

Special hazards arising from the substance or

mixture

Formation of toxic gases is possible during heating or in case of fire

· Advice for firefighters

Protective equipment: Do not inhale explosion gases or combustion gases.

6 Accidental release measures

· Personal precautions, protective equipment

and emergency procedures Not required.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water

Methods and material for containment and

cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust),

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Reference to other sections

Handling:

· Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about protection against explosions and fires:

Keep respiratory protective device available.

(Contd. on page 3)

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN EG 120 { A }

(Contd. of page 2)

Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and

receptacles:

No special requirements.

Information about storage in one common storage facility:

Not required.

Further information about storage conditions: Protect from frost.

Keep receptacle tightly sealed. Store in dry conditions.

Store in a cool place

Specific end use(s)

No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of

technical systems:

No further data; see item 7.

Control parameters

Components with limit values that require

monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have

to be monitored at the workplace.

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working.

Breathing equipment:



Only during spraying without adequate removal by suction.

Use suitable respiratory protective device in case of insufficient ventilation. Use suitable respiratory protective device when high concentrations are present.

Recommended filter device for short term

Protection of hands:

Combination filter A-P2



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves

and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended

As protection from splashes gloves made of

the following materials are suitable:

Nitrile rubber, NBR Natural rubber, NR

Eye protection:



Tightly sealed goggles

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN EG 120 { A }

Body protection:



Not determined.

Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Color: According to product specification

Odor: Characteristic · Odor threshold: Not determined.

· pH-value:

Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 201 °C (394 °F)

Flash point: 201 °C (394 °F)

Flammability (solid, gaseous): Not applicable.

Ignition temperature: > 255 °C (> 491 °F)

· Decomposition temperature: Not determined

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard

· Explosion limits:

Lower: Not determined. Upper: Not determined.

· Vapor pressure at 20 °C (68 °F): 1 hPa (1 mm Hq)

Density at 20 °C (68 °F): 1.33 g/cm3 (11.099 lbs/gal) Relative density Not determined.

Vapor density Not determined · Evaporation rate Not determined.

Solubility in / Miscibility with Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

Viscosity: Dvnamic:

Not determined Kinematic: Not determined.

Solvent content:

Organic solvents: 2.0 % Water: 0.0 %

Solids content: 74.9 % Other information

No further relevant information available.

10 Stability and reactivity

Reactivity

Chemical stability

· Thermal decomposition / conditions to be

· Possibility of hazardous reactions

No decomposition if used according to specifications.

No further relevant information available.

No dangerous reactions known.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

No dangerous decomposition products known.

Trade name: HERCULAN EG 120 { A }

Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available. · Hazardous decomposition products:

11 Toxicological information

· Information on toxicological effects

Acute toxicity:

Primary irritant effect:

on the skin: No irritant effect on the eve: No irritating effect. Sensitization: No sensitizing effects known.

Additional toxicological information: The product shows the following dangers according to internally approved calculation methods

for preparations:

Carcinogenic categories

IARC (International Agency for Research on Cancer) 14808-60-7 Quartz (SiO2) 14807-96-6 Talc (Mg3H2(SiO3)4) 1318-02-1 Zeoliet 1309-37-1 diiron trioxide 14808-60-7 Quartz (SiO2) 13463-67-7 titanium dioxide

NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2) 14808-60-7 Quartz (SiO2)

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

Aquatic toxicity: No further relevant information available. · Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available. Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach

(Contd. on page 6)

HERCUL

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN EG 120 { A }

(Contd. of page 5)

Page 6/8

· Uncleaned packagings:

· Recommendation: Empty contaminated packagings thoroughly. They can be recycled after thorough and proper

Void

cleaning.

14 Transport information

· UN-Number DOT, ADR, ADN, IMDG, IATA Void

· UN proper shipping name

DOT. ADR. ADN. IMDG. IATA Void

· Transport hazard class(es)

DOT. ADR. ADN. IMDG. IATA

· Class

Packing group

DOT, ADR, IMDG, IATA Void

· Environmental hazards:

Marine pollutant: No

· Special precautions for user Not applicable

· Transport in bulk according to Annex II of MARPOL73/78 and

the IBC Code Not applicable

· UN "Model Regulation": Void

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulphate, natural

· TSCA (Toxic Substances Control Act):

8001-79-4 Castor oil

14808-60-7 Quartz (SiO2)

7727-43-7 barium sulphate, natural

14807-96-6 Talc (Mg3H2(SiO3)4)

25322-69-4 Polypropylenglycol

112-27-6 2.2'-(ethylenedioxy)diethanol

68186-91-4 Copper chromite spinel pigment Cu(Cr,Fe)2O4

1309-37-1 diiron trioxide

20344-49-4 iron hydroxide oxide

Proposition 65

· Chemicals known to cause cancer:

14808-60-7 Quartz (SiO2)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 7

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 08/02/2016 Printing date 08/02/2016

3		
Trade name: HERCULAN EG 120 { A }		
	(Contd. of	page 6
· Cancerogenity categories		
· EPA (Environmental Protection Agency)		
7727-43-7 barium sulphate, natural	D, CBD(inh), I	VL(oral)
TLV (Threshold Limit Value established by AC	CGIH)	
14808-60-7 Quartz (SiO2)	· ·	A2
14807-96-6 Talc (Mg3H2(SiO3)4)		A4
1309-37-1 diiron trioxide		A4
14808-60-7 Quartz (SiO2)		A2
13463-67-7 titanium dioxide		A4
MAK (German Maximum Workplace Concentration	ation)	
14808-60-7 Quartz (SiO2)		1
14807-96-6 Talc (Mg3H2(SiO3)4)		ЗВ
14808-60-7 Quartz (SiO2)		1
13463-67-7 titanium dioxide		3A
· NIOSH-Ca (National Institute for Occupational	Safety and Health)	
14808-60-7 Quartz (SiO2)		
14808-60-7 Quartz (SiO2)		
13463-67-7 titanium dioxide		
· GHS label elements	The product is classified and labeled according to the Globally Harmonized System (Gl	HS).
Hazard pictograms	GHS08	
· Signal word	Danger	
Hazard-determining components of labeling	Quartz (SiQ2)	

· Hazard statements H350 May cause cancer.

· Precautionary statements P280

Wear protective gloves/protective clothing/eye protection/face protection.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· National regulations:

· Additional classification according to Decree

on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in

this preparation. Exceptions can be made by the authorities in certain cases.

· Technical instructions (air):

Class | Share in % 2.0 NK

Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· voc

VOC EU [%] 1.95 % VOC EU [g/l] 25.9 g/l VOC USA 25.9 g/l / 0.22 lb/gl

VOC CH 0.00 %

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environmental Department Contact: Dr. Michael Kissel · Date of preparation / last revision 08/02/2016 / 31

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations

Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 8)

HERCUL

* Data compared to the previous version

Page 7/8

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

(Contd. of page 7)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Carc. 1A: Carcinogenicity – Category 1A

Page 8/8