(Contd. of page 1)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

· Product identifier

HERCULAN SX 400 { A } · Trade name:

Article number: 708100/16

Application of the substance / the mixture Coating compound/ Surface coating/ paint

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

HERCULAN B.V. Energieweg 6

4231 DJ Meerkerk The Netherlands Phone +31 183 354700 Fax: +31 183 354740 e-mail: info@herculan.com

Information department: Enviromental department

Emergency telephone number:

+49 (0) 6131 19240 [24 h - 365 d] - Giftinformationszentrale Mainz

+31 (0) 183 354 700 [Mo - Fr. 8 - 17 o'clock] - HERCULAN

2 Hazard(s) identification

Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

H362 May cause harm to breast-fed children. Lact

Label elements

Hazard statements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms GHS08 Signal word Danger

Hazard-determining components of labeling: Quartz (SiO2)

alkanes, C14-17, chloro

Quartz (SiO2)

H350 May cause cancer.

H362 May cause harm to breast-fed children.

Precautionary statements

P263 Avoid contact during pregnancy/while nursing. P260 Do not breathe dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501

Dispose of contents/container in accordance with local/regional/national/ international regulations.

Classification system:

NFPA ratings (scale 0 - 4)

Health = 0Reactivity = 0 0 Health = 0 Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

Other hazards

· Results of PBT and vPvB assessment

PBT:

Not applicable.

HERCUL

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN SX 400 { A }

· vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: There are no additional ingredients present which are classified as hazardous to health or the

environment and on this basis need to be mentioned in this section.

· Dangerous components: 14808-60-7 Quartz (SiO2) & Carc. 1A. H350 25 - 100% 14808-60-7 Quartz (SiO2) & Carc. 1A, H350; STOT RE 2, H373 < 0.2%

No further relevant information available.

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints. · After skin contact: Generally the product does not irritate the skin.

· After eye contact:

If symptoms persist consult doctor.

Rinse opened eye for several minutes under running water.

After swallowing:

Information for doctor:

Most important symptoms and effects, both

acute and delayed

Indication of any immediate medical attention

and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:



CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

Special hazards arising from the substance or

mixture

During heating or in case of fire poisonous gases are produced. Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Protective equipment:

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

6 Accidental release measures

· Personal precautions, protective equipment

and emergency procedures

· Environmental precautions:

Mount respiratory protective device.

Do not allow to enter sewers/ surface or ground water.

cleaning up:

Methods and material for containment and Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)

(Contd. on page 2)

Reviewed on 08/02/2016

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN SX 400 { A }

Nitrile rubber, NBR Natural rubber, NR

Tightly sealed goggles

Printing date 08/02/2016

Trade name: HERCULAN SX 400 { A }

7 Handling and storage

Handling:

Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and

receptacles:

No special requirements.

storage facility:

Information about storage in one common

Not required. Further information about storage conditions: Protect from frost.

Keep receptacle tightly sealed.

Store in dry conditions. Store in a cool place.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of

technical systems:

No further data: see item 7.

· Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have

to be monitored at the workplace.

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working.

Breathing equipment:

Only during spraying without adequate removal by suction.

Use suitable respiratory protective device in case of insufficient ventilation. Use suitable respiratory protective device when high concentrations are present.

Recommended filter device for short term use:

Protection of hands:

Combination filter A-P2



Protective aloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation

of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves

and has to be observed. The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the

penetration time is recommended (Contd. on page 4)

· As protection from splashes gloves made of the following materials are suitable:

HERCUL

Eye protection:

Body protection:

Protective work clothing

9 Ph	ysicai	and	cnen	ııcaı	prope	erties

· Information on basic	physical and chemical	properties
------------------------	-----------------------	------------

General Information

· Appearance:

Form: Fluid

Color: According to product specification

Odor: Characteristic · Odor threshold: Not determined.

· pH-value: Not determined.

Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: 201 °C (394 °F)

Flash point: 255 °C (491 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: > 255 °C (> 491 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard

· Explosion limits:

Lower: Not determined Upper: Not determined.

· Vapor pressure at 20 °C (68 °F): 1 hPa (1 mm Hg)

Density at 20 °C (68 °F): 1.45 g/cm3 (12.1 lbs/gal) Relative density Not determined.

Vapor density Not determined. Evaporation rate Not determined.

Solubility in / Miscibility with

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dvnamic: Not determined Kinematic: Not determined.

Solvent content:

Organic solvents: 0.0 % Water: 0.0 %

Solids content: 75.5 % Other information No further relevant information available.

(Contd. on page 5)

Page 4/8

(Contd. of page 3)

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN SX 400 { A }

(Contd. of page 4)

10 Stability and reactivity

Reactivity

No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be

avoided:

No decomposition if used according to specifications. Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid · Incompatible materials: No further relevant information available. No further relevant information available.

· Hazardous decomposition products:

No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

Primary irritant effect:

on the skin:

No irritant effect. No irritating effect.

on the eve: Sensitization:

No sensitizing effects known.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods

for preparations:

Carcinogenic categories

· IARC (International Agency for Research on Cancer)					
1	Quartz (SiO2) 1	٦			
1318-02-1	Zeoliet 3	٦			
14807-96-6	Talc (Mg3H2(SiO3)4) 3	٦			
	Quartz (SiO2)	٦			
13463-67-7	titanium dioxide 2E	В			

NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

14808-60-7 Quartz (SiO2)

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

Aquatic toxicity:

85535-85-9 alkanes, C14-17, chloro

Accute LC50 1 mg/L (Gammarus pulex)

Acute EC50 0.006 mg/L (Daphnia Magna)

Persistence and degradability

No further relevant information available. Behavior in environmental systems:

Bioaccumulative potential No further relevant information available. Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

· PRT: Not applicable. vPvB: Not applicable.

(Contd. on page 6)

HERCUL

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN SX 400 { A }

No further relevant information available. · Other adverse effects

13 Disposal considerations

Waste treatment methods

· Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach

sewage system.

Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled after thorough and proper

cleaning.

14 Transport information

· UN-Number DOT. ADR. ADN. IMDG. IATA

Void

No

UN proper shipping name

DOT, ADR, ADN, IMDG, IATA Void

· Transport hazard class(es)

DOT, ADR, ADN, IMDG, IATA

· Class Void

Packing group

DOT. ADR. IMDG. IATA Void

· Environmental hazards:

Marine pollutant:

· Special precautions for user Not applicable

Transport in bulk according to Annex II of MARPOL73/78 and

the IBC Code

Not applicable

· UN "Model Regulation": Void

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulphate, natural

· TSCA (Toxic Substances Control Act):

8001-79-4 Castor oil

14808-60-7 Quartz (SiO2)

7727-43-7 barium sulphate, natural

31831-53-5 2-oxepanone, polymer with 1.4 butandiol

25265-71-8 oxydipropanol

14807-96-6 Talc (Mg3H2(SiO3)4)

68186-91-4 Copper chromite spinel pigment Cu(Cr,Fe)204

Proposition 65

· Chemicals known to cause cancer:

14808-60-7 Quartz (SiO2)

(Contd. on page 7)

Page 6/8

(Contd. of page 5)

· National regulations:

Water hazard class:

VOC VOC EU [%]

VOC USA

VOC CH

on Hazardous Materials

Additional classification according to Decree

Information about limitation of use:

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN SX 400 { A } (Contd. of page 6) · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. Chemicals known to cause developmental toxicity: None of the ingredients is listed. Cancerogenity categories EPA (Environmental Protection Agency) 7727-43-7 barium sulphate, natural D. CBD(inh), NL(oral) TLV (Threshold Limit Value established by ACGIH) 14808-60-7 Quartz (SiO2) A4 14807-96-6 Talc (Mg3H2(SiO3)4) 14808-60-7 Quartz (SiO2) A2 13463-67-7 titanium dioxide A4 MAK (German Maximum Workplace Concentration) 14808-60-7 Quartz (SiO2) 14807-96-6 Talc (Mg3H2(SiO3)4) ЗВ 14808-60-7 Quartz (SiO2) 13463-67-7 titanium dioxide NIOSH-Ca (National Institute for Occupational Safety and Health) 14808-60-7 Quartz (SiO2) 14808-60-7 Quartz (SiO2) 13463-67-7 titanium dioxide GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms Signal word Danger · Hazard-determining components of labeling: Quartz (SiO2) alkanes, C14-17, chloro Quartz (SiO2) Hazard statements H350 May cause cancer. H362 May cause harm to breast-fed children. Precautionary statements Avoid contact during pregnancy/while nursing. P260 Do not breathe dust/fume/gas/mist/vapors/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P264 Wash thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P308+P313 IF exposed or concerned: Get medical advice/attention

P405

P501

0.00 %

0.00 %

0.0 g/l / 0.00 lb/gl

Store locked up.

international regulations.

Carcinogenic hazardous material group III (dangerous).

Water hazard class 2 (Self-assessment): hazardous for water.

Dispose of contents/container in accordance with local/regional/national/

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in

this preparation. Exceptions can be made by the authorities in certain cases.

HERCUL

Page 7/8

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN SX 400 { A }

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Dr. Michael Kissel

(Contd. of page 7)

Page 8/8

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environmental Department

Contact:

· Date of preparation / last revision

08/02/2016 / 15

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations · Abbreviations and acronyms: Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) PBT: Persistent. Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safeti OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PFI : Permissible Exposure I imit REL: Recommended Exposure Limit

Carc. 1A: Carcinogenicity - Category 1A Lact.: Reproductive toxicity – effects on or via lactation

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the previous version

altered.

(Contd. on page 8)